

# Test Beam Task List - ECAL

- Aim:
  - ▶ Identify all tasks essential for run and analysis of beam data
  - ▶ Ensure (at least) 1 person commits to produce results in each area
  - ▶ Very variable size of tasks - easier for more people to contribute
- List made from discussions in the UK, so only included UK names
  - ▶ We know their short term interests
  - ▶ Did not know everyone else's
- There is a significant amount of code already existing (Calice-SW; Goetz G.; George M.), and people are needed to use this to carry out the studies
- List of tasks and names will be updated with feedback / volunteers
- Summarise list, then discussion

# Analysis - data/model comparisons

1. Energy resolution vs. energy, angle - YM/NKW + MR +  
*Need containment/complete detector*
2. Position resolution vs. energy, angle - AM/PD/HY + GM + MR +  
*Individual hit resolution in each layer*
3. Angular resolution vs. energy, angle - AM/PD/HY + NKW/YM + MR +
4. Comparison and tuning of simulation to data - CTA + DRW + MR +
5. Comparison of calibrations in cosmics vs. real data - MR +
6. Efficiency, dead space between pads and wafers - GM + MR +  
*Individual sensor response, modelling geometric inefficiency*

# Electronics/DAQ understanding

Using LCIO or (very fast turnaround before conversion) the binary files

1. Coherent noise - CTA + GG

*Study sources of noise, why they vary between configurations, how to minimise using VFE timing sequence.*

2. Crosstalk - CTA + BB

*In VFE calibrations runs, pulse one channel, look at others. Will same cross-talk be present in beam data?*

3. Shaping times - CTA +

*Measure for each preamplifier using VFE calibration runs and cosmuics (or beam) HOLD scans. Determine channel-by-channel correction to gain as necessary*

4. HOLD timing setting - CTA + DB

*Determines HOLD delay to run system, urgent - current cosmic run may not have optimal setting!*

# Reconstruction

1. Tracker calibration - MFG, EG, MGroll. (MFG to travel to DESY for this)  
*Survey/alignment of drift chambers vs. stage; map material upstream of ECAL; track fitting;  $V_{drift}$  (+stability); efficiency with modified gas %*
2. Pedestals vs. time, noise vs. time - CTA +  
*Determination of stability*
3. Pedestals vs. temperature, noise vs. temperature - CTA +  
*Stability with ambient conditions, ∴ precision to monitor temperature in run*
4. Cosmics / data compatibility - GM +  
*Compare gain calibration in 2005 cosmics with new data, understand changes*
5. VFE calibration - GM +  
*Compare with gain calibrations determined from cosmics and/or beam data.  
If useful/compatible → "Run Planning, 2"*
6. Electron beam calibration - NKW/YM +  
*Select subset of reconstructed electron events to extract cleaner MIP peak?  
If works → "Run Planning, 3"*
7. Production data reconstruction - GM +  
*Systematic production of LCIO data with reconstructed objects using best mappings, conditions, .... Make available to collaboration*

# Run planning

1. Optimisation of missing slab positions - DRW + AM/PD/HY  
*Study placement of inactive slabs if too few for 30 layers x 6 wafers*
2. Need for electronics calibration; how often? - CTA + RP  
*Determine frequency required based on stability study*
3. Need for electron beam calibration - YM/NKW +  
*If "Reconstruction 6" possible, define data (spatial distribution into ECAL, no. good events/beam position,  $\therefore$  time required).*

# Run monitoring

1. Immediate online monitoring - PD +  
*Timescale ~ few s: simple, always available, predefined histos, real time.*
2. Semi-online bin file monitoring - GM +  
*Timescale ~ few - 30 mins: operate on binary files from DAQ, present histograms (see talk), event display. Includes diagnostic test programs which can be modified/run on shift for individual channel study. Can output converted LCIO.*
3. (Near-offline) (a) LCIO conversion (could simply use output of 2, above)  
(b) LCIO monitoring - GG + RP  
*Timescale ~ 1 day: offline job which can include any contributed Marlin processor, but does not need dCache. Needs appropriate mapping file ∴ delays if configuration changes. PC, LCIO installation for this provided by HCAL group? Read whatever LCIO files are available on 3TB NFS disk*
4. Book keeping during shifts - ? EG → SK  
*Electronic logbook (must be available off-site), tabular run summary. Expect common logbook with HCAL. Temperature also to record. Profit from GANMVL/EUDET effort c/o Sven K.*
5. Recording test beam conditions - ? EG → SK  
*Beam parameters should be available electronically and put into conditions data, via slow Controls. Ask SK to liase with CERN.*
6. Recording physical configuration - ? EG → SK  
*Survey drift chambers/scintillators/detectors on stage, + many photos of experimental area  
CERN Survey Group should be aware of CALICE requirements before installation.*

# Simulation

1. Digitisation of tracking hits - FS 😊  
*Drift chambers hits for all individual energy deposits, need to remove low energy simulated hits. Find appropriate level. Store as tracker hits*
2. Truth particle information - FS 😊  
*Positions (and  $p$ ) at tracking chambers and also immediately in front of ECAL front face should be stored*
3. Digitisation of ECAL - CTA, AM +  
*Add noise (channel-by-channel), threshold, time-dependence due to preamp shaper, crosstalk, coherent noise. Implement as a Marlin processor, build on existing work.*
4. Production MC simulation - FS, DB  
*Mokka production of standard MC samples, 100k events each angle/energy/stage position and detector configuration. Initially use programme of measurements to be made with beam. Make LCIO available to collaboration.*
5. Production MC reconstruction - MFG/FS + DB  
*Reconstruction, including any default digitisation. Make LCIO files with reconstructed objects available to collaboration.*
6. Simulation of Cerenkov chambers - ??  
*These will form part of the beamline instrumentation at CERN, need to be included in Mokka*

# Discussion

- Over to Goetz/Erika/...
- Additional items for list?
- Overlap with HCAL
- Names